PRODUCTS COVERED BY THIS DECLARATION:

FORK PLATFORM: (Covers all models/model codes, travel settings and configurations)	COIL SPRING	AIR SPRING	MAX SYSTEM WEIGHT LIMIT (kg)
Reba		~	110
Recon Gold		~	110
Judy Gold		\checkmark	135
Paragon		\checkmark	135
Rudy		\checkmark	135
BoXXer		\checkmark	140
35 Gold		\checkmark	150
35 Silver	√*		150
35 Silver		\checkmark	150
Judy Silver	√*		150
Judy Silver		\checkmark	150
Judy TK	√*		150
Lyrik		\checkmark	150
Pike		\checkmark	150
Recon Silver	√*		150
Revelation		\checkmark	150
SID		\checkmark	150
SID SL		\checkmark	150
Yari		~	150
Domain		~	170
Domain Gold		~	170
Psylo Gold		~	170
Psylo Silver	√*	\checkmark	170
ZEB		\checkmark	170

* System weight limit rating for coil sprung forks may exceed available spring rates

WORLD HEADQUARTERS SRAM LLC 1000 W. Fulton Market, 4th Floor Chicago, Illinois 60607

U.S.A.

MANUFACTURING LOCATION 1598-8 Chung-Shan Road

1598-8 Chung-Shan Road Shengang District (42955) Taichung Taiwan

SRAM EUROPE

Paasbosweg 14-16 3862ZS Nijkerk The Netherlands



SRAM LLC hereby declares that the products listed above are in conformity with the essential requirements and other relevant regulations listed below:

STANDARD/DIRECTIVE	HARMONIZED STANDARD / DESCRIPTION			
ISO 4210-2:2023	Cycles - Safety requirements for bicycles - Part 2: Requirements for city and trekking (City +T), young adult (Y), mountain (M) and racing bicycles (R)			
	Section 4.9.1	General		
	Section 4.9.2	Means of location of the axle and wheel retention		
	Section 4.9.3	Tyre clearance test – Suspension fork		
	Section 4.9.4.1	Front fork – Tensile test – Suspension fork		
	Section 4.9.5	Front fork – Static bending test		
	Section 4.9.6	Front fork – Rearward impact test (as applicable)		
	Section 4.9.7	Front fork – Bending fatigue test plus rearward impact test (as applicable)		
	Section 4.9.8	Forks intended for use with hub - or disc-brakes (as applicable)		
	Section 4.9.11	Front mudguard (as applicable)		
ISO 4210-3:2023	Cycles - Safety requirements for bicycles - Part 3: Common test methods			
	Section 4.2.1.1	Test method – Minimal tangential strength (as applicable)		
	Section 4.2.1.2	Test method – Mudguard stays impact test (as applicable)		
	Section 4.2.2	Front mudguard without stays test method (as applicable)		
	Section 4.2.3	Front mudguard – Wheel blocking verification test (as applicable)		
ISO 4210-6:2023	Cycles - Safety requirements for bicycles - Part 6: Frame and fork test methods			
	Section 5.1	Suspension forks – Tyre-clearance test		
	Section 5.2.1	Front fork - Tensile test – Test method – Suspension fork		
	Section 5.3	Front fork – Static bending test – Mountain bicycles		
	Section 5.4	Front fork – Rearward impact test – Mountain bicycles (as applicable)		
	Section 5.5	Front fork – Bending fatigue test and rearward impact test – Mountain bicycles (as applicable)		
	Section 5.6	Forks intended for use with hub or disc brakes – Mountain bicycles (as applicable)		

WORLD HEADQUARTERS

SRAM LLC 1000 W. Fulton Market, 4th Floor Chicago, Illinois 60607 U.S.A.

MANUFACTURING LOCATION

1598-8 Chung-Shan Road Shengang District (42955) Taichung Taiwan

SRAM EUROPE

Paasbosweg 14-16 3862ZS Nijkerk The Netherlands



STANDARD/DIRECTIVE	HARMONIZED STANDARD / DESCRIPTION			
MACHINERY DIRECTIVE 2006/42/EU				
EN 15194:2017+A1:2023	Cycles. Electrically power assisted cycles. EPAC Bicycles			
	Section 4.3.8.1	General		
	Section 4.3.8.2	Means of location of the axle and wheel retention		
	Section 4.3.8.3.1	Tyre-clearance test		
	Section 4.3.8.3.1	Tensile test		
	Section 4.3.8.4	Front fork – Static bending test		
	Section 4.3.8.5	Front fork – Rearward impact test (as applicable)		
	Section 4.3.8.6	Front fork – Bending fatigue test and rearward impact test (as applicable)		
	Section 4.3.8.7	Forks intended for use with hub or disc brakes (as applicable)		
EN 17404:2022	Cycles - Electrically power assisted cycles - EPAC Mountain Bikes			
	Section 4.3.8.1	General		
	Section 4.3.8.2	Front fork – Static bending test		
	Section 4.3.8.3	Front fork – Rearward impact test (as applicable)		
	Section 4.3.8.4	Front fork – Bending fatigue test and rearward impact test (as applicable)		
	Section 4.3.8.5	Forks intended for use with hub or disc brakes (as applicable)		
	Section 4.3.11	Front mudguard (as applicable)		

SIGNATORY:

SRAM LLC

U.S.A.

hand Hund

LEO YERMAKOV Regulatory Compliance Director

WORLD HEADQUARTERS

1000 W. Fulton Market, 4th Floor

DATE: 2024-05-01

Chicago, Illinois 60607

MANUFACTURING LOCATION

1598-8 Chung-Shan Road Shengang District (42955) Taichung Taiwan

.....

SIGNATORY'S ADDRESS

1000 W. Fulton Market, 4th Floor Chicago, Illinois 60607 U.S.A.

SRAM EUROPE

Paasbosweg 14-16 3862ZS Nijkerk The Netherlands