

**ROCKSHOX**

# 2022 Front Suspension Specifications



OIL VOLUME, AIR PRESSURE, COIL SPRING RATES,  
BOTTOMLESS TOKENS, AND TECHNICAL SPECIFICATIONS

# TABLE OF CONTENTS

Suspension Oil and Grease .....	3
Air Spring Pressure.....	8
Coil Spring Rates .....	13
Bottomless Tokens .....	14
Technical Specifications .....	16

# Suspension Oil and Grease

FORK	MODEL	WHEEL (in)	TRAVEL (mm)	DAMPER						SPRING													
				Damper	Upper Tube			Lower Leg		Spring	Upper Tube				Lower Leg								
					Oil	Oil Height <sup>‡</sup> (mm)	Volume (mL)	Oil	Volume (mL)		Oil	Volume (mL)	Grease	Grease Application	Oil	Volume (mL)							
<b>35 Gold</b>	<b>RL RL R<sup>†</sup></b>	27.5 B* 29 B*	100-160	Motion Control RL	5wt	85-90	170	15wt	10	DebonAir	5wt	2	PM600 or SRAM Butter	Air Piston	15wt	10							
<b>35 Silver</b>	<b>TK TK R<sup>†</sup></b>	27.5 B* 29 B*	100-160	Turnkey		90-95	210			Solo Air							Coil	-	-	SRAM Butter	Air Piston	15wt	10
	<b>R</b>			Rebound																			
<b>Bluto</b>	<b>RL RL R<sup>†</sup></b>	26	80-120	Motion Control RL	5wt	71-77	106	15wt	5	Solo Air	-	-	SRAM Butter	Air Piston	15wt	5							
<b>BoXXer</b>	<b>Ultimate</b>	27.5 B* 29 B*	180-200	Charger 2.1 RC2	3wt	-	Bleed	0w-30	10	DebonAir	0w-30	3	RockShox Dynamic Seal Grease	Air Piston	0w-30	10							
	<b>Select</b>			Charger RC			66																
<b>Domain</b>	<b>RC</b>	27.5 B* 29 B*	150-180	Motion Control	3wt	95-100	235	0w-30	10	DebonAir	0w-30	3	RockShox Dynamic Seal Grease	Air Piston	0w-30	10							
	<b>R</b>			Rebound																			
<b>Judy Gold</b>	<b>RL RL R<sup>†</sup></b>	26	80-100	Motion Control RL	5wt	80-85	85	15wt	5	Solo Air	5wt	2	PM600 or SRAM Butter	Air Piston	15wt	10							
		27.5 29	80-120				102		6							6							
		27.5 B* 29 B*															6						

\*Boost  
<sup>†</sup>Remote Adjust  
<sup>‡</sup>Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

# Suspension Oil and Grease

FORK	MODEL	WHEEL (in)	TRAVEL (mm)	DAMPER						SPRING						
				Damper	Upper Tube			Lower Leg		Spring	Upper Tube				Lower Leg	
					Oil	Oil Height <sup>‡</sup> (mm)	Volume (mL)	Oil	Volume (mL)		Oil	Volume (mL)	Grease	Grease Application	Oil	Volume (mL)
Judy Silver	TK TK R <sup>†</sup>	26	80-100	Turnkey	5wt	80-85	100	15wt	5	Solo Air	5wt	2	PM600 or SRAM Butter	Air Piston	15wt	10
		27.5	80-120				123			Coil	-	-		Coil		
		29	80-100				122			Solo Air	5wt	2		Air Piston		
		27.5 B* 29 B*	80-120							Coil	-	-		Coil		
Judy	TK TK R <sup>†</sup>	27.5	80-120	Turnkey	5wt	80-85	143	-	-	Coil	-	-	PM600 or SRAM Butter	Coil	-	-
		29	80-100													
Lyrik	Ultimate	27.5 B* 29 B*	140-180	Charger 2.1 RC2	3wt	-	Bleed	0w-30	10	DebonAir	0w-30	3	RockShox Dynamic Seal Grease	Air Piston	0w-30	10
	Select+			Charger 2.1 RC												
	Select			Charger RC												
	Ultimate		160-180	Charger 2.1 RC2						Dual Position Air						
	Select+			Charger 2.1 RC												
	Select			Charger RC												
Paragon Gold	RL RL R <sup>†</sup>	700c	50-65	Motion Control RL	5wt	80-85	87	15wt	12	Solo Air	5wt	5	PM600 or SRAM Butter	Air Piston	15wt	12

\*Boost  
<sup>†</sup>Remote Adjust  
<sup>‡</sup>Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

# Suspension Oil and Grease

FORK	MODEL	WHEEL (in)	TRAVEL (mm)	DAMPER						SPRING						
				Damper	Upper Tube			Lower Leg		Spring	Upper Tube				Lower Leg	
					Oil	Oil Height <sup>‡</sup> (mm)	Volume (mL)	Oil	Volume (mL)		Oil	Volume (mL)	Grease	Grease Application	Oil	Volume (mL)
PIKE	Ultimate	27.5 B*	120-160	Charger 2.1 RC2 Charger 2.1 RCT3	3wt	-	Bleed	0w-30	10	DebonAir	0w-30	3	RockShox Dynamic Seal Grease	Air Piston	0w-30	10
		29 B*	120-150													
	Select+	27.5 B*	120-160	Charger 2.1 RC												
		29 B*	120-150													
	Select	27.5 B*	120-160	Charger RC												
		29 B*	120-150													
DJ	26	100, 140	Charger													
REBA	26	26	80-140	Rebound	5wt	82-88	136	15wt	5	Solo Air	-	-	PM600 or SRAM Butter	Air Piston	15wt	5
	RL RL R <sup>†</sup>	27.5 B* 29 B*	100	Motion Control RL		71-77	100									
			110-120			105										
Recon Gold	RL RL R <sup>†</sup>	27.5 B 29 B	80-150	Motion Control RL	5wt	80-85	130	15wt	6	DebonAir	5wt	2	PM600 or SRAM Butter	Air Piston	15wt	6
Recon Silver	RL RL R <sup>†</sup>	27.5 29	100-120	Motion Control RL	5wt	80-85	118	15wt	6	Solo Air	5wt	2	PM600 or SRAM Butter	Air Piston	15wt	6
			130-140				150									
		27.5 B* 29 B*	100-150				91-96									
	TK TK R <sup>†</sup>	27.5 29	80-100	Turnkey		80-85	118			Coil	-	-		Coil	9	
			27.5 B* 29 B*			80-120	86-91									140
Revelation	RC RC R <sup>†</sup>	27.5 B*	120-160	Motion Control RC	5wt	100-106	155	0w-30	10	DebonAir	-	-	RockShox Dynamic Seal Grease	Air Piston	0w-30	10
		29 B*	120-150													

\*Boost  
<sup>†</sup>Remote Adjust  
<sup>‡</sup>Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

# Suspension Oil and Grease

FORK	MODEL	WHEEL (in)	TRAVEL (mm)	DAMPER						SPRING						
				Damper	Upper Tube			Lower Leg		Spring	Upper Tube				Lower Leg	
					Oil	Oil Height <sup>‡</sup> (mm)	Volume (mL)	Oil	Volume (mL)		Oil	Volume (mL)	Grease	Grease Application	Oil	Volume (mL)
Rudy XPLR	Ultimate	700c	30-40	Charger Race Day	3wt	-	Bleed	0w-30	10	Solo Air	0w-30	3	RockShox Dynamic Seal Grease	Air Piston	0w-30	10
	Base			Rebound												
SID	Ultimate	29 B*	110-120	Charger Race Day	3wt	-	Bleed	0w-30	10	DebonAir	0w-30	3	RockShox Dynamic Seal Grease	Air Piston	0w-30	10
	Select+			Charger 2 RL												
	Select			Charger RL												
	Base			Rush RL												
SID SL	Ultimate	29 B*	100	Charger Race Day	3wt	-	Bleed	0w-30	10	DebonAir	0w-30	3	RockShox Dynamic Seal Grease	Air Piston	0w-30	10
	Select+			Charger 2 RL												
	Select			Charger RL												
	Base			Rush RL												
Yari	RC	27.5 B* 29 B*	150-180	Motion Control RC	5wt	100-106	180	0w-30	10	DebonAir	0w-30	3	RockShox Dynamic Seal Grease	Air Piston	0w-30	10
		29+	100-160													
		27.5 B* 29 B*	160-180							Dual Position Air	-	-				

<sup>\*</sup>Boost  
<sup>†</sup>Remote Adjust  
<sup>‡</sup>Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

# Suspension Oil and Grease

FORK	MODEL	WHEEL (in)	TRAVEL (mm)	DAMPER					SPRING								
				Damper	Upper Tube			Lower Leg		Spring	Upper Tube				Lower Leg		
					Oil	Oil Height <sup>‡</sup> (mm)	Volume (mL)	Oil	Volume (mL)		Oil	Volume (mL)	Grease	Grease Application	Oil	Volume (mL)	
ZEB	Ultimate	27.5 B* 29 B*	150-190	Charger 2.1 RC2	3wt	-	Bleed	0w-30	20	DebonAir	0w-30	3	RockShox Dynamic Seal Grease	Air Piston	0w-30	20	
	Select+			Charger 2.1 RC													
	Select			Charger RC													
	R			Charger R													
	Ultimate		160-180	Charger 2.1 RC2													Dual Position Air
	Select+			Charger 2.1 RC													
	Select			Charger RC													
	R			Charger R													

\*Boost  
 †Remote Adjust  
 ‡Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

# Air Spring Pressure

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI	
				E-Bikes Add 10 psi								
35 Gold	DebonAir	27.5 B* 29 B*	100-120	<75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115-125 psi	125+ psi	194 psi	
			130-160	<55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	163 psi	
FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)			MAX PSI	
				E-Bikes Add 10 psi								
35 Silver	Solo Air	27.5 B* 29 B*	100-120	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi			265 psi	
FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)			MAX PSI
				E-Bikes Add 10 psi								
35 Silver	Solo Air	27.5 B* 29 B*	130-160	<70 psi	70-90 psi	90-105 psi	105-120 psi	120-135 psi	135+ psi			195 psi
FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI	
				E-Bikes Add 10 psi								
BoXXer	DebonAir	27.5 B* 29 B*	180	<105 psi	105-115 psi	115-125 psi	125-135 psi	135-145 psi	145-155 psi	155+ psi	200 psi	
			190-200	<95 psi	95-105 psi	105-115 psi	115-125 psi	125-135 psi	135-145 psi	145+ psi		
FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)			MAX PSI	
				E-Bikes Add 10 psi								
Bluto	Solo Air	26	80-120	70-90 psi	90-105 psi	105-120 psi	120-135 psi	135+ psi			200 psi	
FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI	
				E-Bikes Add 10 psi								
Domain	DebonAir	27.5 B* 29 B*	150-160	<45 psi	45-54 psi	54-62 psi	62-70 psi	70-78 psi	78-87 psi	87+ psi	148 psi	
			170-180	<37 psi	37-45 psi	45-54 psi	54-62 psi	62-70 psi	70-78 psi	78+ psi		

\*Boost



# Air Spring Pressure

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)	MAX PSI
				E-Bikes Add 10 psi					
Judy Gold	Solo Air	26 27.5 29	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	265 psi
			100						
		27.5 29	120	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	205 psi
		27.5 B* 29 B*	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	265 psi
			100-120	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	205 psi
Judy Silver	Solo Air	26 27.5 29	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	265 psi
			100						
		27.5	120	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	205 psi
		27.5 B* 29 B*	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	265 psi
			100-130	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	205 psi

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes Add 10 psi							
Lyrik	DebonAir	27.5 B* 29 B*	140	<65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115+ psi	163 psi
			150-160	<55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	
			170-180	<45 psi	45-55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95+ psi	148 psi

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				Featured on E-MTB models only							
Lyrik	Dual Position Air	27.5 B* 29 B*	160	<65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115+ psi	163 psi
			170-180	<55 psi	55-65 psi	65-75 psi	75-85 p si	85-95 psi	95-105 psi	105+ psi	148 psi

# Air Spring Pressure

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<132 lbs (<60 kg)	132-155 lbs (60-70 kg)	155-176 lbs (70-80 kg)	176-198 lbs (80-90 kg)	>198 lbs (>90 kg)	MAX PSI
				E-Bikes Add 10 psi					
<b>Paragon Gold</b>	Solo Air	700c	50-65	80-90 psi	90-100 psi	100-125 psi	125-135 psi	135+ psi	165 psi

  

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes Add 10 psi							
<b>PIKE</b>	DebonAir	27.5 B* 29 B*	120	<70 psi	70-80 psi	80-90 psi	90-100 psi	100-110 psi	110-120 psi	120+ psi	163 psi
			130-140	<60 psi	60-70 psi	70-80 psi	80-90 psi	90-100 psi	100-110 psi	110+ psi	
		27.5 B*	150-160	<50 psi	50-60 psi	60-70 psi	70-80 psi	80-90 psi	90-100 psi	100+ psi	
		29 B*	150								

  

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes Add 10 psi						
<b>PIKE DJ</b>	Solo Air	26	100	100-115 psi	115-130 psi	130-145 psi	145-160 psi	160-175 psi	175+ psi	250 psi
			140	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115+ psi	163 psi

  

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<60lbs (<27 kg)	60-80 lbs (27-36 kg)	80-100 lbs (36-45 kg)	100-120 lbs (45-54 kg)	120 lbs (54 kg)	MAX PSI
				E-Bikes Add 10 psi					
<b>REBA 26</b>	Solo Air	26	80-140	<25 psi	25-40 psi	40-55 psi	55-75 psi	75+ psi	190 psi

  

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)	MAX PSI
				E-Bikes Add 10 psi						
<b>REBA</b>	Solo Air	27.5 B* 29 B*	100-120	<70 psi	70-90 psi	90-105 psi	105-120 psi	120-135 psi	135+ psi	195 psi

# Air Spring Pressure

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)	MAX PSI
				E-Bikes Add 10 psi					
Recon Gold	DebonAir	27.5 B* 29 B*	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	265 psi
			100-120	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	205 psi
			130-150	40-60 psi	60-75 psi	75-90 psi	90-105 psi	105+ psi	225 psi
Recon Silver RL	Solo Air	27.5 29	100-140	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	205 psi
		27.5 B* 29 B*	100-150						

  

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes Add 10 psi							
Revelation	DebonAir	27.5 B* 29 B*	120	<75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115-125 psi	125+ psi	194 psi
			130-140	<65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115+ psi	163 psi
			150	<55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	
		27.5 B*	160								

  

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)	MAX PSI
				E-Bikes Add 10 psi						
Rudy XPLR	Solo Air	700c	30	<90 psi	90-110 psi	110-130 psi	130-150 psi	150-170 psi	170+ psi	200 psi
			40							

  

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)	MAX PSI
				E-Bikes Add 10 psi						
SID SL	DebonAir	29 B*	100	<70 psi	70-90 psi	90-105 psi	105-120 psi	120-135 psi	135+ psi	195 psi
SID			110-120	<45 psi	45-59 psi	59-73 psi	73-87 psi	87-101 psi	101+ psi	146 psi

\*Boost

# Air Spring Pressure

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes Add 10 psi							
Yari	DebonAir	27.5 B* 29 B*	150-160	<55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	163 psi
			170-180	<45 psi	45-55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95+ psi	148 psi
		29+	100	<85 psi	85-95 psi	95-105 psi	105-115 psi	115-125 psi	125-135 psi	135+ psi	194 psi
			110-120	<75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115-125 psi	125+ psi	
			130-140	<65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115+ psi	163 psi
			150-160	<55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	

  

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				Featured on E-MTB models only							
Yari	Dual Position Air	27.5 B* 29 B*	160	<65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115+ psi	163 psi
			170-180	<55 psi	55-65 psi	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105+ psi	148 psi

  

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes Add 10 psi							
ZEB	DebonAir	27.5 B* 29 B*	150-160	<45 psi	45-54 psi	54-62 psi	62-70 psi	70-78 psi	78-87 psi	87+ psi	148 psi
			170-180	<37 psi	37-45 psi	45-54 psi	54-62 psi	62-70 psi	70-78 psi	78+ psi	
			190	<29 psi	29-37 psi	37-46 psi	46-54 psi	54-62 psi	62-70 psi	70+ psi	

  

FORK	AIR SPRING	WHEEL (in)	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				Featured on E-MTB models only							
ZEB	Dual Position Air	27.5 B* 29 B*	160	<55 psi	55-64 psi	64-72 psi	72-80 psi	80-88 psi	88-97 psi	97+ psi	148 psi
			170-180	<47 psi	47-55 psi	55-64 psi	64-72 psi	72-80 psi	80-88 psi	88+ psi	

# Coil Spring Rates

FORK	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)
35 Silver (Dual Position Coil)	-	Red Medium	-	-	Black X-Firm
35 Silver TK 35 Silver R	Silver X-Soft	Yellow Soft	Red Medium	Blue Firm	Black X-Firm
Judy Silver TK					
Judy TK					
Recon Silver TK					

# Bottomless Tokens

FORK	SPRING	WHEEL (in)	TRAVEL (mm)	FACTORY INSTALLED TOKENS	MAXIMUM TOKENS
<b>35 Gold</b>	DebonAir	27.5 B* 29 B*	100	1	2
			120	1	2
			130	0	2
			140	0	2
			150	0	2
			160	0	2
<b>35 Silver</b>	Solo Air	27.5 B* 29 B*	100	1	2
			120	1	2
			130	0	2
			140	0	2
			150	0	2
			160	0	2
<b>Bluto</b>	Solo Air	26	80	4	4
			100	2	4
			120	0	4
<b>BoXXer</b>	DebonAir	29 B*	180	2	6
			190	1	6
		27.5 B* 29 B*	200	0	6
<b>Domain</b>	DebonAir	27.5 B* 29 B*	150	2	3
			160	2	3
			170	1	3
			180	0	3

FORK	SPRING	WHEEL (in)	TRAVEL (mm)	FACTORY INSTALLED TOKENS	MAXIMUM TOKENS
<b>Lyrik</b>	DebonAir	27.5 B* 29 B*	140	3	5
			150	2	5
			160	2	5
			170	1	4
			180	0	4
	Dual Position Air	27.5 B* 29 B*	160	2	5
170			1	4	
180			0	4	
<b>PIKE DJ</b>	Solo Air	26	100	0	2
			140	2	4
<b>PIKE</b>	DebonAir	27.5 B* 29 B*	120	3	6
			130	2	6
			140	1	5
		150	0	4	
		27.5 B*	160	0	4
<b>REBA 26</b>	Solo Air	26	80	2	3
			100	2	3
			120	0	3
			130	2	4
			140	1	4
<b>REBA</b>	Solo Air	27. B* 29 B*	100	0	3
			110	1	3
			120	0	3

# Bottomless Tokens

FORK	SPRING	WHEEL (in)	TRAVEL (mm)	FACTORY INSTALLED TOKENS	MAXIMUM TOKENS
Revelation	DebonAir	27.5 B* 29 B*	120	4	6
			130	3	6
			140	2	5
			150	1	4
		27.5 B*	160	0	4
Recon Gold	DebonAir	27.5 B* 29 B*	80	0	2
			100	0	2
			120	0	2
			130	0	2
			140	0	2
			150	0	2
SID SL	DebonAir	29 B*	100	0	3
SID			110	1	3
			120	0	3

FORK	SPRING	WHEEL (in)	TRAVEL (mm)	FACTORY INSTALLED TOKENS	MAXIMUM TOKENS
Yari	DebonAir	27.5 B* 29 B*	150	2	5
			160	2	5
			170	1	4
			180	0	4
			100	5	7
		110	5	7	
		120	4	7	
		130	3	6	
		140	3	6	
		150	2	5	
	160	2	5		
	Dual Position Air	27.5 B* 29 B*	160	2	5
			170	1	4
			180	0	4
150			2	5	
ZEB	DebonAir	27.5 B* 29 B*	150	2	5
			160	2	5
			170	1	4
			180	0	4
			190	0	4
	Dual Position Air	27.5 B* 29 B*	160	2	5
			170	1	4
			180	0	4
			160	2	5

# Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL (in)	TRAVEL (mm)	SPRING	DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)											
35 Gold	35	27.5 B*	100	DebonAir	Motion Control RL	1.5 Tapered Alum 1.8 Tapered Alum†	15 x 110	37, 44	492, 498 (F)	180	220	732, 728 (F)	81											
			120						512, 518 (F)															
			130						522, 528 (F)															
			140						532, 538 (F)															
			150						542, 548 (F)															
			160						552, 558 (F)															
		29 B*	100					511, 517 (F)	770, 766 (F)															
			120					531, 537 (F)																
			130					541, 547 (F)																
			140					551, 557 (F)																
			150					561, 567 (F)																
			160					571, 577 (F)																
			35 Silver					35				27.5 B*		100	Solo Air Coil	Turnkey	1.5 Tapered Alum 1.8 Tapered Alum†	15 x 110	37, 44	492, 498 (F)	180	220	732, 728 (F)	81
														120						512, 518 (F)				
130	522, 528 (F)																							
140	532, 538 (F)																							
150	542, 548 (F)																							
160	552, 558 (F)																							

\*Boost  
†44 mm Offset  
(F) RockShox Bolt-on Fender Compatible



# Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL (in)	TRAVEL (mm)	SPRING	DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
35 Silver	35	29 B*	100	Solo Air Coil	Turnkey	1.5 Tapered Alum 1.8 Tapered Alum†	15 x 110	44, 51	511, 517 (F)	180	220	770, 766 (F)	
			120						531, 537 (F)				
			130						541, 547 (F)				
			140						551, 557 (F)				
			150						561, 567 (F)				
			160						571, 577 (F)				
		27.5 B*	100	Dual Position Coil	Rebound			492, 498 (F)					
			120					512, 518 (F)					
			130					522, 528 (F)					
			140					532, 538 (F)					
			150					542, 548 (F)					
			160					552, 558 (F)					
		29 B*	100	Coil				511, 517 (F)					
			120					531, 537 (F)					
			130					541, 547 (F)					
			140					551, 557 (F)					
			150					561, 567 (F)					
			160					571, 577 (F)					
Bluto	32	26	80	Solo Air	Motion Control RL	1.5 Tapered Alum	15 x 150	51	491	160	220	760	116
			100						511				
			120						531				

\*Boost  
†44 mm Offset  
(F) RockShox Bolt-on Fender Compatible

# Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL (in)	TRAVEL (mm)	SPRING	DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)						
BoXXer Ultimate BoXXer Select	35	27.5 B*	200	DebonAir	Charger 2.1 RC2 Charger RC	1 1/8 Alum	20 x 110	36, 46	581	200	220	732	81						
		29 B*	180					46, 56	582			770							
			190						592										
			200						602										
Domain	38	27.5 B*	150	DebonAir	Motion Control RC Rebound	1.5 Tapered Alum 1.8 Tapered Alum†	15 x 110	38, 44	547	200	220	732 (F)	81						
			160						557										
			170						567										
			180						577										
		29 B*	150					44, 51	566			770 (F)							
			160						576										
			170						586										
			180						596										
Judy Gold	30	26	80	Solo Air	Motion Control RL	1 1/8 Alum	9 QR	40	453	160	185	680	58						
			100						473					710					
		27.5	80					42	468			755							
			100						488										
			120						508										
		29	80					46 51	487			62							
			100			507													
			120			527													

\*Boost  
†44 mm Offset  
(F) RockShox Bolt-on Fender Compatible

# Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL (in)	TRAVEL (mm)	SPRING	DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)	
Judy Gold	30	27.5 B*	80	Solo Air	Motion Control RL	1.5 Tapered Alum	15 x 110	42 51	472	160	220	732	81	
			100						492					
			120						512					
		29 B*	80					490						
			100					510						
			120					530						
Judy Silver	30	26	80	Solo Air	Turnkey	1 1/8 Aluminum 1.5 Tapered Alum	9 QR	40	455	160	185	680	58	
			100	475										
		27.5	80	Solo Air Coil		1 1/8 Alum 1 1/8 Steel 1.5 Tapered Alum		470	710					
			100					490						
			120					510						
		29	80	Solo Air		1.5 Tapered Alum		489	755					
			100					509						
		27.5 B*	80	Solo Air		1.5 Tapered Alum		15 x 110	42 51		470, 476 (F)	220	732, 728 (F)	81
			100								490, 496 (F)		732	
			120								510, 516 (F)		770	
			130								520		770	
		29 B*	80	Solo Air		1.5 Tapered Alum		15 x 110	51		490, 496 (F)	220	770, 766 (F)	81
			100								510, 516 (F)		770	
			120								530, 536 (F)		770	
			130								540		770	

\*Boost  
 †44 mm Offset  
 (F) RockShox Bolt-on Fender Compatible

# Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL (in)	TRAVEL (mm)	SPRING	DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
Judy	30	27.5	80	Coil	Turnkey	1 1/8 Alum 1 1/8 Steel 1.5 Tapered Alum	9 QR	42	470	160	185	710	62
			100						490				
			120						510				
		29	80			1 1/8 Steel 1.5 Tapered Alum		46	489			755	
			100					51	509				
Lyrik Ultimate Lyrik Select+ Lyrik Select	35	27.5 B*	140	DebonAir	Charger 2.1 RC2 Charger 2.1 RC Charger RC	1.5 Tapered Alum 1.8 Tapered Alum†	15 x 110	37 44 46	532	180	220	732	81
			150						542				
			160						552				
			170						562				
			180						572				
			29 B*						140				
		150				561							
		160				571							
		170				581							
		180				591							
		Paragon Gold	30			700c		50	Solo Air			Motion Control RL	
65	477 (F)												
PIKE Ultimate PIKE Select+ PIKE Select	35	27.5 B*	120	DebonAir	Charger 2.1 RC2 Charger 2.1 RCT3 Charger 2.1 RC Charger RC	1.5 Tapered Alum	15 x 110	37 46	512	180	220	732	81
			130						522				
			140						532				
			150						542				
			160						552				

\*Boost  
†44 mm Offset  
(F) RockShox Bolt-on Fender Compatible

# Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL (in)	TRAVEL (mm)	SPRING	DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)	
<b>PIKE Ultimate</b> <b>PIKE Select+</b> <b>PIKE Select</b>	35	29 B*	120	DebonAir	Charger 2.1 RC2 Charger 2.1 RCT3 Charger 2.1 RC Charger RC	1.5 Tapered Alum	15 x 110	42 51	531	180	220	770	81	
			130						541					
			140						551					
			150						561					
<b>PIKE DJ</b>	35	26	100	Solo Air	Charger	1.5 Tapered Alum	15 x 100	40	482	160	220	694	66	
			140						522					
<b>REBA 26</b>	32	26	80	Solo Air	Rebound	1.5 Tapered Alum	15 x 100	40	460	160	220	691	63	
			100						480					
			120						500					
			130						510					
			140						520					
<b>REBA</b>	32	27.5 B*	100	Solo Air	Motion Control RL	1.5 Tapered Alum	15 x 110	42	487	160	220	714	81	
			110						497					
			120						507					
		29 B*	100					506	755					
			110					521						
			120					531						760

\*Boost  
 †44 mm Offset  
 (F) RockShox Bolt-on Fender Compatible

# Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL (in)	TRAVEL (mm)	SPRING	DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)										
Recon Gold RL	32	27.5 B*	80	DebonAir	Motion Control RL	1.5 Tapered Alum	15 x 110	37 46	474, 480 (F)	160	220	732, 728 (F)	81										
			100						494, 500 (F)														
			120						514, 520 (F)														
			130						524, 530 (F)														
			140						534, 540 (F)														
			150						544, 550 (F)														
			29 B*						80					493, 499 (F)									
		100						513, 519 (F)															
		120						533, 539 (F)															
		130						543, 549 (F)															
		140						553, 559 (F)															
		150						563, 569 (F)															
		Recon Silver RL						32	27.5					100	Solo Air	Motion Control RL	1 1/8 Alum	9 QR	42	486	160	220	710
			120											1.5 Tapered Alum			506						
100	1.5 Tapered Alum		15 x 100	486																			
120				506																			
130				520																			
140				530																			

\*Boost  
 †44 mm Offset  
 (F) RockShox Bolt-on Fender Compatible

# Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL (in)	TRAVEL (mm)	SPRING	DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
Recon Silver RL	32	27.5 B*	100	Solo Air	Motion Control RL	1.5 Tapered Alum	15 x 110	37, 46	494, 500 (F)	160	220	732, 728 (F)	81
			120						514, 520 (F)				
			130						524, 530 (F)				
			140						534, 540 (F)				
			150						544, 550 (F)				
		29	100			1 1/8 Alum 1.5 Tapered Alum	9 QR 15 x 100	46, 51	505				
			120			1.5 Tapered Alum	15 x 100		529				
			130						539				
			140						549				
		29 B*	100					1.5 Tapered Alum	15 x 110			42, 51	513, 519 (F)
			120			533, 539 (F)							
			130			543, 549 (F)							
			140			553, 559 (F)							
			150			563, 569 (F)							
		Recon Silver TK	32			27.5	80	Coil	Turnkey			1 1/8 Steel 1.5 Tapered Alum	9 QR 15 x 100
100	486												
120	506												
27.5 B*	80			1.5 Tapered Alum	15 x 110	37 46	474, 480 (F)						
	100						494, 500 (F)						
	120						514, 520 (F)						

\*Boost  
 †44 mm Offset  
 (F) RockShox Bolt-on Fender Compatible

# Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL (in)	TRAVEL (mm)	SPRING	DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)						
Recon Silver TK	32	29	80	Coil	Turnkey	1 1/8 Steel 1.5 Tapered Alum	9 QR 15 x 100	46 51	485	160	220	755	62						
			100						505										
			120						525										
	29 B*	80	493, 499 (F)			770													
		100	513, 519 (F)																
		120	533, 539 (F)																
		130	543, 539 (F)																
		140	553, 559 (F)																
		150	563, 569 (F)																
		770, 766 (F)																	
81																			
Revelation	35	27.5 B*	120	DebonAir	Motion Control RC	1.5 Tapered Alum	15 x 110	37 46	512	180	220	732	81						
			130						522										
			140						532										
			150						542										
			160						552										
		29 B*	120					531	770										
			130					541											
			140					551											
	150		561																
	42 51																		
	Rudy XPLR Ultimate Rudy XPLR Base	30	700c			30	Solo Air	Charger Race Day Rebound	1.5 Tapered Alum 1.8 Tapered Alum†			12 x 100		45 51	425	180	160	716 (F)	50
						40									435				

\*Boost  
†44 mm Offset  
(F) RockShox Bolt-on Fender Compatible



# Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL (in)	TRAVEL (mm)	SPRING	DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
SID SL Ultimate SID SL Select+ SID SL Select SID SL Base	32	29 B*	100	DebonAir	Charger Race Day Charger 2 RL Charger RL Rush RL	1.5 Tapered Alum	15 x 110	44	506	160	200	751	60
SID Ultimate SID Select+ SID Select SID Base	35	29 B*	110 120	DebonAir	Charger Race Day Charger 2 RL Charger RL Rush RL	1.5 Tapered Alum	15 x 110	44	521 531	180	220	758 (F)	66
Yari	35	27.5 B*	150	DebonAir	Motion Control RC	1.5 Tapered Alum 1.8 Tapered Alum†	15 x 110	37 44 46	542	180	220	732	81
			160	DebonAir					552				
			170	Dual Position Air					562				
			180	Dual Position Air					572				
		29 B*	150	DebonAir				561					
			160	DebonAir				571					
			170	Dual Position Air				581					
			180	Dual Position Air				591					
		29+	100	DebonAir				523					
			110					533					
			120					543					
			130					553					
			140					563					
			150					573					
			160					583					
			160					583					

\*Boost  
†44 mm Offset  
(F) RockShox Bolt-on Fender Compatible

# Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL (in)	TRAVEL (mm)	SPRING	DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
<b>ZEB Ultimate</b> <b>ZEB Select+</b> <b>ZEB Select</b> <b>ZEB</b>	38	27.5 B*	150	DebonAir	Charger 2.1 RC2 Charger 2.1 RC Charger RC Charger R	1.5 Tapered Alum 1.8 Tapered Alum†	15 x 110	38 44	547	200	220	732 (F)	81
			160						557				
			170						567				
			180						577				
			190						587				
		29 B*	150					566					
			160					576					
			170					586					
			180					596					
			190					606					
		27.5 B*	160	Dual Position Air	557								
			170		567								
			180		577								
		29 B*	160		576								
			170		586								
			180		596								

\*Boost  
†44 mm Offset  
(F) RockShox Bolt-on Fender Compatible

**These are registered trademarks of SRAM, LLC:**

1:1®, Accuwatt®, Avid®, ATAC®, AXS®, Bar®, Bioposition®, Blackbox®, BoXXer®, DoubleTap®, eTap®, Firecrest®, Firex®, Grip Shift®, GXP®, Holzfeller®, Hussefelt®, Icllic®, i-Motion®, Judy®, Know Your Powers®, NSW®, Omnium®, Osmos®, Pike®, PowerCal®, PowerLock®, PowerTap®, Qollector®, Quarq®, RacerMate®, Reba®, Rock Shox®, Ruktion®, Service Course®, ShockWiz®, SID®, Single Digit®, Speed Dial®, Speed Weaponry®, Spinscan®, SRAM®, SRAM APEX®, SRAM EAGLE®, SRAM FORCE®, SRAM RED®, SRAM RIVAL®, Stylo®, TIME®, Truvativ®, TyreWiz®, UDH®, Varicrank®, Velotron®, X0®, X01®, X-SYNC®, XX1®, Zipp®

**These are registered logos of SRAM, LLC:**



**These are trademarks of SRAM, LLC:**

10K™, 1X™, 202™, 30™, 30 Course™, 35™, 302™, 303™, 353™, 404™, 454™, 808™, 858™, 3ZERO MOTO™, ABLC™, AeroGlide™, AeroBalance™, AeroLink™, Airea™, Air Guides™, AKA™, AL-7050-TV™, Atmos™, Automatic Drive™, AxCad™, Axial Clutch™, Base™, BB5™, BB7™, BB30™, Bleeding Edge™, Blipbox™, BlipClamp™, BlipGrip™, Blips™, Bluto™, Bottomless Tokens™, Cage Lock™, Carbon Bridge™, Centera™, Charger 2™, Charger™, Charger Race Day™, Cleansweep™, Clickbox Technology™, Clics™, Code™, Cognition™, CoLab™, Connectamajig™, Counter Measure™, CYCLO™, DD3™, DD3 Pulse™, DebonAir™, Deluxe™, Deluxe Re:Aktiv™, Descendant™, DFour™, DFour91™, DH™, Dig Valve™, DirectLink™, Direct Route™, Domain™, DOT 5.1™, Double Decker™, Double Time™, Dual Flow Adjust™, Dual Position Air™, DUB™, DUB-PWR™, DZero™, E300™, E400™, Eagle™, E-Connect4™, ErgoBlade™, ErgoDynamics™, ESP™, EX1™, Exact Actuation™, Exogram™, Flow Link™, FR-5™, Full Pin™, G2™, G40™, Giga Pipe™, Gnar Dog™, Guide™, GS™, GX™, Hard Chrome™, Hexfin™, HollowPin™, Howitzer™, HRD™, Hybrid Drive™, Hyperfoil™, i-3™, Impress™, Jaws™, Jet™, Kage™, Komfy™, LINK™, Lyrik™, MatchMaker™, Maxle™, Maxle 360™, Maxle DH™, Maxle Lite™, Maxle Lite DH™, Maxle Stealth™, Maxle Ultimate™, Micro Gear System™, Mini Block™, Mini Cluster™, Monarch™, Monarch Plus™, Motion Control™, Motion Control DNA™, MRX™, MX™, Noir™, NX™, OCT™, OmniCal™, OneLoc™, Paceline™, Paragon™, PC-1031™, PC-1110™, PC-1170™, PG-1130™, PG-1050™, PG-1170™, Piggyback™, Poploc™, Power Balance™, Power Bulge™, PowerChain™, PowerDomeX™, Powered by SRAM™, PowerGlide™, PowerLink™, Power Pack™, Power Spline™, Predictive Steering™, Pressfit™, Pressfit 30™, Prime™, Qalvin™, R2C™, Rapid Recovery™, Re:Aktiv ThruShaft™, Recon™, Reverb™, Revelation™, Riken™, Roller Bearing Clutch™, Rolling Thunder™, RS-1™, Rudy™, Rush™, RXS™, Sag Gradients™, Sawtooth™, SCT - Smart Coasterbrake Technology™, Seeker™, Sektor™, SHIFT™, ShiftGuide™, Shorty™, Showstopper™, SIDLuxe™, Side Swap™, Signal Gear Technology™, SL™, SL-70™, SL-70 Aero™, SL-70 Ergo™, SL-80™, SI-88™, SLC2™, SL SPEED™, SL Sprint™, Smart Connect™, Solo Air™, Solo Spoke™, Speciale™, SpeedBall™, Speed Metal™, SRAM APEX 1™, SRAM Force 1™, SRAM RIVAL 1™, S-series™, Stealth-a-majig™, StealthRing™, Super-9™, Supercork™, Super Deluxe™, Super Deluxe Coil™, SwingLink™, SX™, Tangente™, TaperCore™, Timing Port Closure™, TSE Technology™, Tool-free Reach Adjust™, Top Loading Pads™, Torque Caps™, TRX™, Turnkey™, TwistLoc™, VCLC™, Vivid™, Vivid Air™, Vuka Aero™, Vuka Alumina™, Vuka Bull™, Vuka Clip™, Vuka Fit™, Wide Angle™, WiFLi™, X1™, X3™, X4™, X5™, X7™, X9™, X-Actuation™, XC™, X-Dome™, XD™, XDR™, XG-1150™, XG-1175™, XG-1180™, XG-1190™, X-Glide™, X-GlideR™, X-Horizon™, XLoc Sprint™, XPLR™, XPRESSO™, XPRO™, X-Range™, XX™, Yari™, ZEB™, Zero Loss™, ZM2™, ZR1™



Specifications and colors subject to change without prior notice.

© 2021 SRAM, LLC

**This publication includes trademarks and registered trademarks of the following companies:**

Boost™ is a trademark owned by Trek Bicycle Corporation.

---

ASIAN HEADQUARTERS

SRAM Taiwan  
No. 1598-8 Chung Shan Road  
Shen Kang Hsiang, Taichung City  
Taiwan R.O.C.

WORLD HEADQUARTERS

SRAM LLC  
1000 W. Fulton Market, 4th Floor  
Chicago, Illinois 60607  
U.S.A.

EUROPEAN HEADQUARTERS

SRAM Europe  
Paasbosweg 14-16  
3862ZS Nijkerk  
The Netherlands