

ROCKSHOX

2026 Front Suspension Specifications



OIL VOLUME, AIR PRESSURE, COIL SPRING RATE, AND SPECIFICATIONS

TABLE OF CONTENTS

Suspension Oil and Grease.....	3
Air Spring Pressure.....	8
Coil Spring Rates	12
Technical Specifications.....	13

Use ONLY RockShox and/or Maxima suspension oils/fluids and grease as specified. Use of any other oils/fluids and grease can damage seals and decrease performance.

Refer to the appropriate RockShox suspension fork service manual, available at www.sram.com/service, for service specifications and procedures.

For SRAM Warranty information, visit: www.sram.com/warranty.

For SRAM Trademark information, visit: www.sram.com/website-terms-of-use.

Suspension Oil and Grease

				DAMPER						SPRING								
FORK	MODEL	WHEEL	TRAVEL (mm)	DAMPER	UPPER TUBE			LOWER LEG		SPRING	UPPER TUBE				LOWER LEG			
					Oil**	Oil Height (mm)	Volume (mL)	Oil**	Volume (mL)		Oil**	Volume (mL)		Grease	Grease Application	Oil**	Volume (mL)	
												(+)	(-)					
BoXXer FS-BXR-ULT-D1 FS-BXR-BSE-D1	Ultimate	27.5" B 29" B	180-200	Charger 3 RC2	Maxima PLUSH 7wt	-	Bleed	Maxima PLUSH Dynamic Suspension Lube Light	40	DebonAir+	Maxima PLUSH Dynamic Suspension Lube Heavy	3	1	SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Light	20	
	Base			Charger 3 RC														
Domain FS-DOMN-GRC-C1 FS-DOMN-GR-C1	RC	27.5" B 29" B	130-180	Isolator RC	Maxima PLUSH 7wt	96	220	Maxima PLUSH Dynamic Suspension Lube Light	15	DebonAir	Maxima PLUSH Dynamic Suspension Lube Heavy	2	2	SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Light	15	
	R			Rebound														
Judy Gold FS-JDYG-RL-A3	RL RL R†	26"	80-100	Motion Control RL	RockShox 5wt	80-85	85	RockShox 15wt	5	Solo Air	RockShox 5wt	2	-	PM600 or SRAM Butter	Air Piston	RockShox 15wt	10	
		27.5" 29"	80-120				102										6	6
		27.5" B 29" B																
Judy Silver FS-JDYS-TK-A3	TK TK R†	26"	80-100	Turnkey	RockShox 5wt	80-85	100	RockShox 15wt	5	Solo Air	RockShox 5wt	2	-	PM600 or SRAM Butter	Air Piston	RockShox 15wt	10	
		27.5"	80-120				123			Coil	-	-	Coil					
		29"	80-100				122			Solo Air	RockShox 5wt	2	-		Air Piston			
		27.5" B 29" B	80-120							Coil	-	-	-		Coil			
										Solo Air	RockShox 5wt	2	-		Air Piston			6
Judy FS-JDY-TK-B1	TK TK R†	27.5"	80-120	Turnkey	RockShox 5wt	80-85	143	-	-	Coil	-	-	-	PM600 or SRAM Butter	Coil	-	-	
		29"	80-100															

B = Boost

**Suspension oil/fluid - Maxima PLUSH Dynamic Suspension Lube and RockShox 0w-30 suspension oils are forward and backward compatible with RockShox Dynamic Seal Grease and SRAM Butter.

†Remote Adjust

‡Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

Suspension Oil and Grease

				DAMPER						SPRING							
FORK	MODEL	WHEEL	TRAVEL (mm)	DAMPER	UPPER TUBE			LOWER LEG		SPRING	UPPER TUBE					LOWER LEG	
					Oil**	Oil Height: (mm)	Volume (mL)	Oil**	Volume (mL)		Oil**	Volume (mL)		Grease	Grease Application	Oil**	Volume (mL)
												(+)	(-)				
Lyrik FS-LYRK-UFA-D2 FS-LYRK-ULT-D2 FS-LYRK-SELP-D2 FS-LYRK-SEL-D1 FS-LYRK-BSE-D1	Ultimate Flight Attendant	27.5" B 29" B	140-160	Charger 3.1 Flight Attendant	Maxima PLUSH 7wt	-	Bleed	Maxima PLUSH Dynamic Suspension Lube Light	30	DebonAir+	Maxima PLUSH Dynamic Suspension Lube Heavy	3	1	SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Light	15
	Charger 3.1 RC2																
	Charger RC			Maxima PLUSH 3wt													
	Rush RC																
	Base																
Paragon Gold FS-PARG-RL-A1	RL RL R†	700c	50-65	Motion Control RL	RockShox 5wt	80-85	87	RockShox 15wt	12	Solo Air	RockShox 5wt	3	-	PM600 or SRAM Butter	Air Piston	RockShox 15wt	12
Pike FS-PIKE-UFA-C2 FS-PIKE-ULT-C2 FS-PIKE-SELP-C2 FS-PIKE-SEL-C1 FS-PIKE-BSE-C1 FS-PIKE-DJ-A4	Ultimate Flight Attendant	27.5" B 29" B	120-140	Charger 3.1 Flight Attendant	Maxima PLUSH 7wt	-	Bleed	Maxima PLUSH Dynamic Suspension Lube Light	30	DebonAir+	Maxima PLUSH Dynamic Suspension Lube Light	3	1	SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Light	15
	Charger 3.1 RC2																
	Charger RC			Maxima PLUSH 3wt													
	Rush RC																
	Base																
	DJ	26"	100, 140	Charger					10	Solo Air	-	-	-			10	
Psylo FS-PSYL-GRC-A1 FS-PSYL-GRCF-A1	RC	27.5" B 29" B	130-160	Isolator RC	Maxima PLUSH 7wt	96	168	Maxima PLUSH Dynamic Suspension Lube Light	10	DebonAir	Maxima PLUSH Dynamic Suspension Lube Heavy	2	2	SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Light	10
Psylo FS-PSYL-SRC-A1 FS-PSYL-SRCF-A1	RC	27.5" B 29" B	130-160	Motion Control RC	Maxima PLUSH 7wt	106	190	Maxima PLUSH Dynamic Suspension Lube Light	10	Solo Air	Maxima PLUSH Dynamic Suspension Lube Heavy	2	2	SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Light	10
Psylo FS-PSYL-SR-A1 FS-PSYL-SRF-A1	R	27.5" B 29" B	130-160	Rebound	Maxima PLUSH 7wt	106	190	Maxima PLUSH Dynamic Suspension Lube Light	10	Coil	-	-	-	SRAM Butter	Coil	Maxima PLUSH Dynamic Suspension Lube Light	10

B = Boost

**Suspension oil/fluid - Maxima PLUSH Dynamic Suspension Lube and RockShox Oil-30 suspension oils are forward and backward compatible with RockShox Dynamic Seal Grease and SRAM Butter.

†Remote Adjust

‡Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

Suspension Oil and Grease

				DAMPER						SPRING							
FORK	MODEL	WHEEL	TRAVEL (mm)	DAMPER	UPPER TUBE			LOWER LEG		SPRING	UPPER TUBE					LOWER LEG	
					Oil**	Oil Height: (mm)	Volume (mL)	Oil**	Volume (mL)		Oil**	Volume (mL)		Grease	Grease Application	Oil**	Volume (mL)
												(+)	(-)				
Reba FS-REBA-15NB-A8	26	26"	80-140	Rebound	RockShox 5wt	82-88	136	RockShox 15wt	5	Solo Air	-	-	-	PM600 or SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Light	5
Reba Gold FS-REBA-GLD-B1 FS-REBA-GLDA-B1	Gold	27.5" B 29" B	80-130	Isolator	Maxima PLUSH 7wt	96	155	Maxima PLUSH Dynamic Suspension Lube Heavy	15	DebonAir	Maxima PLUSH Dynamic Suspension Lube Heavy	4	-	SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Heavy	15
Reba RL FS-REBA-RL-B1 FS-REBA-RLA-B1	RL	27.5" B 29" B		Motion Control			150										
Recon Gold FS-RCNG-RL-C1	RL RL R†	27.5" B 29" B	80-150	Motion Control RL	RockShox 5wt	80-85	130	RockShox 15wt	6	DebonAir	RockShox 5wt	2	-	PM600 or SRAM Butter	Air Piston	RockShox 15wt	6
Recon Silver FS-RCNS-RL-D1 FS-RCNS-TK-D1	RL RL R†	27.5" 29"	100-120	Motion Control RL	RockShox 5wt	80-85	118	RockShox 15wt	6	Solo Air	RockShox 5wt	2	-	PM600 or SRAM Butter	Air Piston	RockShox 15wt	6
			130-140				150										
		27.5" B 29" B	100-150				140										
	TK TK R†	27.5" 29"	80-100	Turnkey		80-85	118			Coil	-	-	-		Coil		9
			80-120				140										
							86-91										
Rudy XPLR FS-RUDY-ULT-A2 FS-RUDY-BSE-A1	Ultimate	700c	30-40	Charger Race Day 2	Maxima PLUSH 3wt	-	Bleed	Maxima PLUSH Dynamic Suspension Lube Heavy	15	Solo Air	Maxima PLUSH Dynamic Suspension Lube Heavy	5	-	SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Heavy	15
	Base			Rebound													

B = Boost

**Suspension oil/fluid - Maxima PLUSH Dynamic Suspension Lube and RockShox 0w-30 suspension oils are forward and backward compatible with RockShox Dynamic Seal Grease and SRAM Butter.

†Remote Adjust

‡Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

Suspension Oil and Grease

				DAMPER						SPRING							
FORK	MODEL	WHEEL	TRAVEL (mm)	DAMPER	UPPER TUBE			LOWER LEG		SPRING	UPPER TUBE				LOWER LEG		
					Oil**	Oil Height: (mm)	Volume (mL)	Oil**	Volume (mL)		Oil**	Volume (mL)		Grease	Grease Application	Oil**	Volume (mL)
												(+)	(-)				
SID SL FS-SIDS-UFA-E1 FS-SIDS-ULT3-E1 FS-SIDS-ULT2-E1 FS-SIDS-SLP3-E1 FS-SIDS-SLP2-E1 FS-SIDS-SEL3-E1 FS-SIDS-SEL2-E1 FS-SIDS-BSE3-E1 FS-SIDS-BSE2-E1	Ultimate Flight Attendant	29" B	100-110	Charger Race Day 2 Flight Attendant	Maxima PLUSH 3wt	-	Bleed	Maxima PLUSH Dynamic Suspension Lube Heavy	9	DebonAir+	Maxima PLUSH Dynamic Suspension Lube Heavy	3	-	SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Heavy	9
	Ultimate			Charger Race Day 2 3 Position 2 Position													
	Select+			Charger RL 3 Position 2 Position													
	Select			Rush RL 3 Position 2 Position													
	Base																
SID FS-SID-UFA-D1 FS-SID-ULT3-D1 FS-SID-ULT2-D1 FS-SID-SLP3-D1 FS-SID-SLP2-D1 FS-SID-SEL3-D1 FS-SID-SEL2-D1 FS-SID-BSE3-D1 FS-SID-BSE2-D1	Ultimate Flight Attendant	29" B	100-120	Charger Race Day 2 Flight Attendant	Maxima PLUSH 3wt	-	Bleed	Maxima PLUSH Dynamic Suspension Lube Heavy	15	DebonAir+	Maxima PLUSH Dynamic Suspension Lube Heavy	3	-	SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Heavy	15
	Ultimate			Charger Race Day 2 3 Position 2 Position													
	Select+			Charger RL 3 Position 2 Position													
	Select																
	Base																

B = Boost

**Suspension oil/fluid - Maxima PLUSH Dynamic Suspension Lube and RockShox 0w-30 suspension oils are forward and backward compatible with RockShox Dynamic Seal Grease and SRAM Butter.

*Remote Adjust

†Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

Suspension Oil and Grease

				DAMPER						SPRING							
FORK	MODEL	WHEEL	TRAVEL (mm)	DAMPER	UPPER TUBE			LOWER LEG		SPRING	UPPER TUBE					LOWER LEG	
					Oil**	Oil Height: (mm)	Volume (mL)	Oil**	Volume (mL)		Oil**	Volume (mL)		Grease	Grease Application	Oil**	Volume (mL)
												(+)	(-)				
ZEB FS-ZEB-UFA-A3 FS-ZEB-ULT-A3 FS-ZEB-SELP-A3 FS-ZEB-SEL-A2 FS-ZEB-BSE-A2	Ultimate Flight Attendant	27.5" B 29" B	150-190	Charger 3.1 Flight Attendant	Maxima PLUSH 7wt	-	Bleed	Maxima PLUSH Dynamic Suspension Lube Light	30	DebonAir+	Maxima PLUSH Dynamic Suspension Lube Light	3	1	SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Light	15
	Ultimate			Charger 3.1 RC2													
	Select+			Charger RC													
	Select			Rush RC	Maxima PLUSH 3wt												
	Base																
ZEB FS-ZEB-SEL-A2 FS-ZEB-BSE-A2	Ultimate	27.5" B 29" B	160-180	Charger 3 RC2	Maxima PLUSH 7wt	-	Bleed	Maxima PLUSH Dynamic Suspension Lube Light	30	Dual Position Air	Maxima PLUSH Dynamic Suspension Lube Light	3	1	SRAM Butter	Air Piston	Maxima PLUSH Dynamic Suspension Lube Light	15
	Select+			Charger RC	Maxima PLUSH 3wt												
	Select																
	Base			Rush RC													

B = Boost

**Suspension oil/fluid - Maxima PLUSH Dynamic Suspension Lube and RockShox 0w-30 suspension oils are forward and backward compatible with RockShox Dynamic Seal Grease and SRAM Butter.

*Remote Adjust

†Oil Height - Measure from the top of the crown (above the upper tube) down to the oil.

Air Spring Pressure

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes add 10 psi							
BoXXer FS-BXR-ULT-D1 FS-BXR-BSE-D1	DebonAir+	27.5" B 29" B	180	<115 psi	115-140 psi	140-165 psi	165-190 psi	190-215 psi	215-240 psi	240+ psi	300 psi
			190-200	<90 psi	90-110 psi	110-130 psi	130-150 psi	150-170 psi	170-190 psi	190+ psi	

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes add 10 psi							
Domain FS-DOMN-GRC-C1 FS-DOMN-GR-C1	DebonAir	27.5" B 29" B	130-150	<45 psi	45-54 psi	54-62 psi	62-70 psi	70-78 psi	78-87 psi	87+ psi	148 psi
			160-180	<37 psi	37-45 psi	45-54 psi	54-62 psi	62-70 psi	70-78 psi	78+ psi	

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)	MAX PSI
				E-Bikes add 10 psi					
Judy Gold FS-JDYG-RL-A3	Solo Air	26" 27.5" 29"	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	265 psi
			100	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	205 psi
		27.5" 29"	120						
		27.5" B 29" B	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	265 psi
			100-120	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	205 psi
		Judy Silver FS-JDYS-TK-A3	26" 27.5" 29"	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi
100				50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	205 psi
27.5"			120						
27.5" B 29" B			80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	265 psi
			100-130	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	205 psi

Air Spring Pressure

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes add 10 psi							
Lyrik FS-LYRK-UFA-D2 FS-LYRK-ULT-D2 FS-LYRK-SELP-D2 FS-LYRK-SEL-D1 FS-LYRK-BSE-D1	DebonAir+	27.5" B 29" B	140	<60 psi	60-70 psi	70-80 psi	80-90 psi	90-100 psi	100-110 psi	110+ psi	163 psi
			150-160	<50 psi	50-60 psi	60-70 psi	70-80 psi	80-90 psi	90-100 psi	100+ psi	

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<132 lbs (<60 kg)	132-155 lbs (60-70 kg)	155-176 lbs (70-80 kg)	176-198 lbs (80-90 kg)	>198 lbs (>90 kg)	MAX PSI
				E-Bikes add 10 psi					
Paragon Gold FS-PARG-RL-A1	Solo Air	700c	50-65	80-90 psi	90-100 psi	100-125 psi	125-135 psi	135+ psi	165 psi

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes add 10 psi							
Pike FS-PIKE-UFA-C2 FS-PIKE-ULT-C2 FS-PIKE-SELP-C2 FS-PIKE-SEL-C1 FS-PIKE-BSE-C1	DebonAir+	27.5" B 29" B	120	<60 psi	60-70 psi	70-80 psi	80-90 psi	90-100 psi	100-110 psi	110+ psi	163 psi
			130-140	<50 psi	50-60 psi	60-70 psi	70-80 psi	80-90 psi	90-100 psi	100+ psi	

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes add 10 psi						
Pike DJ FS-PIKE-DJ-A4	Solo Air	26"	100	100-115 psi	115-130 psi	130-145 psi	145-160 psi	160-175 psi	175+ psi	250 psi
			140	65-75 psi	75-85 psi	85-95 psi	95-105 psi	105-115 psi	115+ psi	163 psi

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes add 10 psi							
Psylo Gold FS-PSYL-GRC-A1 FS-PSYL-GRCF-A1	DebonAir	27.5" B 29" B	130 (100-120)	<100 psi	100-110 psi	110-120 psi	120-130 psi	130-140 psi	140-150 psi	150+ psi	194 psi
			140-160	<75 psi	75-85 psi	85- 95 psi	95-105 psi	105-115 psi	115-125 psi	125+ psi	

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes add 10 psi							
Psylo Silver FS-PSYL-SRC-A1 FS-PSYL-SRCF-A1	Solo Air	27.5" B 29" B	130 (100-120)	<100 psi	100-120 psi	120-140 psi	140-160 psi	160-180 psi	180-200 psi	200+ psi	250 psi
			140-160	<80 psi	80-100 psi	100- 120 psi	120-140 psi	140-160 psi	160-180 psi	180+ psi	

Air Spring Pressure

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<60lbs (<27 kg)	60-80 lbs (27-36 kg)	80-100 lbs (36-45 kg)	100-120 lbs (45-54 kg)	120 lbs (54 kg)	MAX PSI
Reba 26 FS-REBA-15NB-A8	Solo Air	26"	80-140	<25 psi	25-40 psi	40-55 psi	55-75 psi	75+ psi	190 psi

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<100 lbs (<45 kg)	100-120 lbs (45-55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)	MAX PSI	
				E-Bikes add 10 psi								
Reba Gold FS-REBA-GLD-B1 FS-REBA-GLDA-B1	DebonAir	27.5" B 29" B	80-100	<39 psi	39-51 psi	51-64 psi	64-76 psi	76-87 psi	87-99 psi	100+ psi	150 psi	
			110-130	<29 psi	29-41 psi	41-54 psi	54-66 psi	66-77 psi	77-89 psi	90+ psi		

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<100 lbs (<45 kg)	100-120 lbs (45-55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)	MAX PSI
				E-Bikes add 10 psi							
Reba RL FS-REBA-RL-B1 FS-REBA-RLA-B1	DebonAir	27.5" B 29" B	80-100	<39 psi	39-51 psi	51-64 psi	64-76 psi	76-87 psi	87-99 psi	100+ psi	150 psi
			110-130	<29 psi	29-41 psi	41-54 psi	54-66 psi	66-77 psi	77-89 psi	90+ psi	

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)	MAX PSI
				E-Bikes add 10 psi					
Recon Gold FS-RCNG-RL-C1	DebonAir	27.5" B 29" B	80	90-110 psi	110-125 psi	125-140 psi	140-160 psi	160+ psi	265 psi
			100-120	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	205 psi
			130-150	130-150 psi	60-75 psi	75-90 psi	90-105 psi	105+ psi	225 psi

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)	MAX PSI
				E-Bikes add 10 psi					
Recon Silver RL FS-RCNS-RL-D1	Solo Air	27.5" 29"	100-140	50-70 psi	70-85 psi	85-100 psi	100-120 psi	120+ psi	205 psi
		27.5" B 29" B	100-150						

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<120 lbs (~55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (~90 kg)	MAX PSI
				E-Bikes add 10 psi						
Rudy XPLR FS-RUDY-ULT-A2 FS-RUDY-BSE-A1	Solo Air	700c	30	<90 psi	90-110 psi	110-130 psi	130-150 psi	150-170 psi	170+ psi	200 psi
			40							

Air Spring Pressure

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)	MAX PSI
				E-Bikes add 10 psi						
SID SL FS-SIDS-UFA-E1 FS-SIDS-ULT3-E1 FS-SIDS-ULT2-E1 FS-SIDS-SLP3-E1 FS-SIDS-SLP2-E1 FS-SIDS-SEL3-E1 FS-SIDS-SEL2-E1 FS-SIDS-BSE3-E1 FS-SIDS-BSE2-E1	DebonAir+	29" B	100-110	<85 psi	85-95 psi	95-108 psi	108-120 psi	120-132 psi	132+ psi	195 psi

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<100 lbs (<45 kg)	100-120 lbs (45-55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	>200 lbs (>90 kg)	MAX PSI
				E-Bikes add 10 psi							
SID FS-SID-UFA-D1 FS-SID-ULT3-D1 FS-SID-ULT2-D1 FS-SID-SLP3-D1 FS-SID-SLP2-D1 FS-SID-SEL3-D1 FS-SID-SEL2-D1 FS-SID-BSE3-D1 FS-SID-BSE2-D1	DebonAir+	29" B	100-120	<39 psi	39-51 psi	51-64 psi	64-76 psi	76-87 psi	87-99 psi	100+ psi	150 psi

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes add 10 psi							
ZEB FS-ZEB-UFA-A3 FS-ZEB-ULT-A3 FS-ZEB-SELP-A3 FS-ZEB-SEL-A2 FS-ZEB-BSE-A2	DebonAir+	27.5" B 29" B	150-160	<45 psi	45-54 psi	54-62 psi	62-70 psi	70-78 psi	78-87 psi	87+ psi	148 psi
			170-180	<37 psi	37-45 psi	45-54 psi	54-62 psi	62-70 psi	70-78 psi	78+ psi	
			190	<29 psi	29-37 psi	37-46 psi	46-54 psi	54-62 psi	62-70 psi	70+ psi	

FORK	AIR SPRING	WHEEL	TRAVEL (mm)	<120 lbs (<55 kg)	120-140 lbs (55-63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)	>220 lbs (>99 kg)	MAX PSI
				E-Bikes add 10 psi							
ZEB FS-ZEB-SEL-A2 FS-ZEB-BSE-A2	Dual Position Air	27.5" B 29" B	160	<55 psi	55-64 psi	64-72 psi	72-80 psi	80-88 psi	88-97 psi	97+ psi	148 psi
			170-180	<47 psi	47-55 psi	55-64 psi	64-72 psi	72-80 psi	80-88 psi	88+ psi	

Coil Spring Rates

FORK	<140 lbs (<63 kg)	140-160 lbs (63-72 kg)	160-180 lbs (72-81 kg)	180-200 lbs (81-90 kg)	200-220 lbs (90-99 kg)
Judy Silver FS-JDYS-TK-A3	Silver X-Soft	Yellow Soft	Red Medium	Blue Firm	Black X-Firm
Judy FS-JDY-TK-B1					
Psylo Silver R FS-PSYL-SR-A1 FS-PSYL-SRF-A1					
Recon Silver FS-RCNS-TK-D1					

Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL	TRAVEL (mm)	SPRING	BOTTOMLESS TOKENS		DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)									
					INSTALLED	MAX																		
BoXXer Ultimate FS-BXR-ULT-D1 BoXXer Base FS-BXR-BSE-D1	38	27.5" B	180	DebonAir+ w/ ButterCups DebonAir+	1	6	Charger 3 RC2 w/ ButterCups Charger 3 RC	1 1/8 Alum	20 x 110	44, 48	566	200	220	732, 730 (F)	81, 78 (F)									
			190		0						576													
			200		586																			
		29" B	180		1					48, 52	585			770, 761 (F)										
			190		0						595													
			200								605													
		Domain FS-DOMN-GRC-C1	38	27.5" B	130					DebonAir	2			3		Isolator RC Isolator R	1.5 Tapered Alum 1.8 Tapered Alum	15 x 110	44	527	200	220	732 (F)	81
					140															537				
150	547																							
160	557																							
170	1				567																			
180	0				577																			
29" B	130			2	546	770 (F)																		
	140				556																			
	150				566																			
	160				576																			
	170			1	586																			
	180			0	596																			

Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL	TRAVEL (mm)	SPRING	BOTTOMLESS TOKENS		DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)		
					INSTALLED	MAX											
Domain FS-DOMN-GR-C1	38	27.5" B	150	DebonAir	2	3	Isolator R	1.5 Tapered Alum 1.8 Tapered Alum†	15 x 110	44	547	200	220	732 (F)	81		
			160								557						
			170		1						567						
			180		0						577						
		29" B	150		2						566			770 (F)			
			160								576						
			170		1						586						
			180		0						596						
			Judy Gold FS-JDYG-RL-A3	30	27.5"	80	Solo Air	-	-	Motion Control RL	1 1/8 Alum 1.5 Tapered Alum	9 QR	42	160	185	710	62
						100											
120		508															
29"	80				487	755											
	100	46, 51			507												
	120				527												
27.5" B	80				472	220					732						
	100	42, 51			492												
	120				512												
29" B	80				490						770						
	100	51	510														
	120		530														

Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL	TRAVEL (mm)	SPRING	BOTTOMLESS TOKENS		DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)		
					INSTALLED	MAX											
Judy Silver FS-JDYS-TK-A3	30	27.5"	80	Solo Air Coil	-	-	Turnkey	1 1/8 Alum 1 1/8 Steel 1.5 Tapered Alum	9 QR	42	470	160	185	710	62		
			100								490						
			120								510						
		29"	80							46, 51	489			755			
			100								509						
		27.5" B	80							Solo Air	1.5 Tapered Alum			15 x 110		42, 51	470, 476 (F)
			100	490, 496 (F)													
			120	510, 516 (F)													
			130	520, 526 (F)													
		29" B	80	490, 496 (F)				770, 766 (F)									
			100	510, 516 (F)													
			120	530, 536 (F)													
			130	540, 546 (F)													
		Judy FS-JDY-TK-B1	30	27.5"				80	Coil	-			-		Turnkey	1 1/8 Alum 1 1/8 Steel 1.5 Tapered Alum	9 QR
100	490																
120	510																
29"	80			46, 51	489	755											
	100				509												

Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL	TRAVEL (mm)	SPRING	BOTTOMLESS TOKENS		DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)								
					INSTALLED	MAX																	
Lyrik Ultimate Flight Attendant FS-LYRK-UFA-D2	35	27.5" B	140	DebonAir+ w/ ButterCups	1	5	Charger 3.1 Flight Attendant w/ ButterCups	1.5 Tapered Alum	15 x 110	37, 44	532	180	220	732 (F)	81								
			150		0						542												
			160		0						552												
		29" B	140		1					44	551			770 (F)									
			150		0						561												
			160		0						571												
Lyrik Ultimate FS-LYRK-ULT-D2 Lyrik Select+ FS-LYRK-SELP-D2 Lyrik Select FS-LYRK-SEL-D1 Lyrik Base FS-LYRK-BSE-D1	35	27.5" B	140	DebonAir+ w/ ButterCups	1	5	Charger 3.1 RC2 w/ ButterCups Charger 3 RC2	1.5 Tapered Alum 1.8 Tapered Alum	15 x 110	37, 44	532	180	220	732 (F)	81								
			150		0						542												
			160		0						552												
		29" B	140	DebonAir+	1		44			551	770 (F)												
			150	DebonAir+	0					561													
			160	0	571																		
		Paragon Gold FS-PARG-RL-A1	30	700c	50		Solo Air			-	-			Motion Control RL		1 1/8 Alum 1 1/8 Alum XL 1.5 Tapered Alum	9 QR	46	462	160	180	716 (F)	45
					65					477													
		Pike Ultimate Flight Attendant FS-PIKE-UFA-C2 Pike Ultimate FS-PIKE-ULT-C2 Pike Select+ FS-PIKE-SELP-C2 Pike Select FS-PIKE-SEL-C1 Pike Base FS-PIKE-BSE-C1	35	27.5" B	120		DebonAir+ w/ ButterCups			1	6			Charger 3.1 Flight Attendant w/ ButterCups		1.5 Tapered Alum	15 x 110	37, 44	512	180	220	732 (F)	81
130	0				522																		
140	5				532																		
29" B	120			DebonAir+	1	44	531	770 (F)															
	130			DebonAir+	0		541																
	140			0	5		551																

Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL	TRAVEL (mm)	SPRING	BOTTOMLESS TOKENS		DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)													
					INSTALLED	MAX																						
Pike DJ FS-PIKE-DJ-A4	35	26"	100	Solo Air	0	2	Charger	1.5 Tapered Alum	15 x 100	40	482	160	220	694	66													
			140		2	4					522																	
Psylo FS-PSYL-GRC-A1 FS-PSYL-GRCF-A1	35	27.5" B	130	DebonAir	0	2	Isolator RC	1.5 Tapered Alum 1.8 Tapered Alum†	15 x 110	37, 44	531 (FF), 522 (SF)	180	220	732	81													
			140								541 (FF), 532 (SF)																	
			150								551 (FF), 542 (SF)																	
			160								561 (FF), 552 (SF)																	
		29" B	130							44	550 (FF), 541 (SF)			770														
			140								560 (FF), 551 (SF)																	
			150								570 (FF), 561 (SF)																	
			160								580 (FF), 571 (SF)																	
			Psylo FS-PSYL-SRC-A1 FS-PSYL-SRCF-A1								35					27.5" B	130	Solo Air	1	2	Motion Control RC	1.5 Tapered Alum 1.8 Tapered Alum†	37, 44	531 (FF), 522 (SF)	180	220	732	81
																	140							541 (FF), 532 (SF)				
																	150							551 (FF), 542 (SF)				
																	160							561 (FF), 552 (SF)				
29" B	130	44		550 (FF), 541 (SF)	770																							
	140			560 (FF), 551 (SF)																								
	150			570 (FF), 561 (SF)																								
	160			580 (FF), 571 (SF)																								

Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL	TRAVEL (mm)	SPRING	BOTTOMLESS TOKENS		DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
					INSTALLED	MAX									
Psylo FS-PSYL-SR-A1 FS-PSYL-SRF-A1	35	27.5" B	130	Coil	-	-	Rebound	1.5 Tapered Alum 1.8 Tapered Alum†	15 x 110	37, 44	531 (FF), 522 (SF)	180	220	732	81
			140								541 (FF), 532 (SF)				
			150								551 (FF), 542 (SF)				
			160								561 (FF), 552 (SF)				
		29" B	130							44	550 (FF), 541 (SF)			770	
			140								560 (FF), 551 (SF)				
			150								570 (FF), 561 (SF)				
			160								580 (FF), 571 (SF)				
Reba 26 FS-REBA-15NB-A8	32	26"	80	Solo Air	2	4	Rebound	1.5 Tapered Alum	15 x 100	40	460	160	220	691	63
			100		0						480				
			120								500				
			130								510				
			140								520				

Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL	TRAVEL (mm)	SPRING	BOTTOMLESS TOKENS		DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)												
					INSTALLED	MAX																					
Reba Gold FS-REBA-GLD-B1 FS-REBA-GLDA-B1	35	27.5" B	80	DebonAir	3	3	Isolator RL	1.5 Tapered Alum	15 x 110	44	475	180	200	720	81												
			100		2	3					494																
			110		1	3					505																
			120		0	2					514																
			130		0	2					525																
		29" B	80		3	3					494			758													
			100		2	3					514																
			110		1	3					524																
			120		0	2					534																
			130		0	2					544																
			Reba RL FS-REBA-RL-B1 FS-REBA-RLA-B1		35	27.5" B					80					DebonAir	3	3	Motion Control	1.5 Tapered Alum	15 x 110	44	475	180	200	720	81
											100						2	3					494				
110	1	3		505																							
120	0	2		514																							
130	0	2		525																							
29" B	80	3		3		494	758																				
	100	2		3		514																					
	110	1		3		524																					
	120	0		2		534																					
	130	0		2		544																					

Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL	TRAVEL (mm)	SPRING	BOTTOMLESS TOKENS		DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
					INSTALLED	MAX									
Recon Gold RL FS-RCNG-RL-C1	32	27.5" B	80	DebonAir	0	2	Motion Control RL	1.5 Tapered Alum	15 x 110	37, 46	474, 480 (F)	160	220	732 (F)	81
			100								494, 500 (F)				
			120								514, 520 (F)				
			130								524, 530 (F)				
			140								534, 540 (F)				
			150								544, 550 (F)				
		29" B	80							42, 51	493, 499 (F)			770 (F)	
			100								513, 519 (F)				
			120								533, 539 (F)				
			130								543, 549 (F)				
			140								553, 559 (F)				
			150								563, 569 (F)				

Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL	TRAVEL (mm)	SPRING	BOTTOMLESS TOKENS		DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
					INSTALLED	MAX									
Recon Silver RL FS-RCNS-RL-D1	32	27.5"	100	Solo Air	-	-	Motion Control RL	1 1/8 Alum 1.5 Tapered Alum	9 QR	42	486	160	220	710	62
			120					506							
			100					15 x 100	486						
			120						506						
			130						520						
			140						530						
		27.5" B	100					1.5 Tapered Alum	15 x 110	37, 46	494, 500 (F)			732 (F)	81
			120								514, 520 (F)				
			130								524, 530 (F)				
			140								534, 540 (F)				
			150								544, 550 (F)				
		29"	100					1 1/8 Alum 1.5 Tapered Alum	9 QR 15 x 100	46, 51	505			755	62
			120								529				
			130					15 x 100	539						
			140						549						
		29" B	100					1.5 Tapered Alum	15 x 110	42, 51	513, 519 (F)			770 (F)	81
			120								533, 539 (F)				
			130								543, 549 (F)				
			140								553, 559 (F)				
			150								563, 569 (F)				

Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL	TRAVEL (mm)	SPRING	BOTTOMLESS TOKENS		DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
					INSTALLED	MAX									
Recon Silver TK FS-RCNS-TK-D1	32	27.5"	80	Coil	-	-	Turnkey	1 1/8 Steel	9 QR	42	466	160	220	710	62
			100								486				
			80								466				
			100								486				
		27.5" B	80					1.5 Tapered Alum	15 x 110	37, 46	474, 480 (F)			732 (F)	81
			100								494, 500 (F)				
			120								514, 520 (F)				
		29"	80					1 1/8 Steel 1.5 Tapered Alum	9 QR 15 x 100	46, 51	485			755	62
			100								505				
		29" B	80					1.5 Tapered Alum	15 x 110	42, 51	493, 499 (F)			770 (F)	81
			100								513, 519 (F)				
			120								533, 539 (F)				
Rudy XPLR Ultimate FS-RUDY-ULT-A2 Rudy XPLR Base FS-RUDY-BSE-A1	30	700c	30	Solo Air	-	-	Charger Race Day 2	1.5 Tapered Alum 1.8 Tapered Alum	12 x 100	45, 51	425	160	180	716 (F)	50
			40				Rebound				435				

Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL	TRAVEL (mm)	SPRING	BOTTOMLESS TOKENS		DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)
					INSTALLED	MAX									
SID SL Ultimate Flight Attendant FS-SIDS-UFA-E1	32	29" B	100 110	DebonAir+	0	3	Charger Race Day 2 Flight Attendant 3 Position (Open/Pedal/Lock)	1.5 Tapered Alum	15 x 110	44	511 521	160	200	755	62
SID SL Ultimate 3P FS-SIDS-ULT3-E1							Charger Race Day 2 3 Position (Open/Pedal/Lock)								
SID SL Ultimate 2P FS-SIDS-ULT2-E1							Charger Race Day 2 2 Position (Open/Lock)								
SID SL Select+ 3P FS-SIDS-SLP3-E1							Charger RL 3 Position (Open/Pedal/Lock)								
SID SL Select+ 2P FS-SIDS-SLP2-E1							Charger RL 2 Position (Open/Lock)								
SID SL Select 3P FS-SIDS-SEL3-E1	35	29" B	100 110 120	DebonAir+	1 1 0	3	Rush RL 3 Position (Open/Pedal/Lock)	1.5 Tapered Alum	15 x 110	44	511 521 531	180	220	758	66
SID SL Select 2P FS-SIDS-SEL2-E1							Rush RL 2 Position (Open/Lock)								
SID SL Base 3P FS-SIDS-BSE2-E1							Charger Race Day 2 Flight Attendant 3 Position (Open/Pedal/Lock)								
SID SL Base 2P FS-SIDS-BSE2-E1							Charger Race Day 2 3 Position (Open/Pedal/Lock)								
SID SL Base 2P FS-SIDS-BSE2-E1							Charger Race Day 2 2 Position (Open/Lock)								
SID Ultimate Flight Attendant FS-SID-UFA-D1	35	29" B	100 110 120	DebonAir+	1 1 0	3	Charger Race Day 2 Flight Attendant 3 Position (Open/Pedal/Lock)	1.5 Tapered Alum	15 x 110	44	511 521 531	180	220	758	66
SID Ultimate 3P FS-SID-ULT3-D1							Charger Race Day 2 3 Position (Open/Pedal/Lock)								
SID Ultimate 2P FS-SID-ULT2-D1							Charger Race Day 2 2 Position (Open/Lock)								
SID Select+ 3P FS-SID-SLP3-D1							Charger RL 3 Position (Open/Pedal/Lock)								
SID Select+ 2P FS-SID-SLP2-D1							Charger RL 2 Position (Open/Lock)								
SID Select 3P FS-SID-SEL3-D1	35	29" B	100 110 120	DebonAir+	1 1 0	3	Rush RL 3 Position (Open/Pedal/Lock)	1.5 Tapered Alum	15 x 110	44	511 521 531	180	220	758	66
SID Select 2P FS-SID-SEL2-D1							Rush RL 2 Position (Open/Lock)								
SID Base 3P FS-SID-BSE2-D1							Charger Race Day 2 Flight Attendant 3 Position (Open/Pedal/Lock)								
SID Base 2P FS-SID-BSE2-D1							Charger Race Day 2 3 Position (Open/Pedal/Lock)								
SID Base 2P FS-SID-BSE2-D1							Charger Race Day 2 2 Position (Open/Lock)								

Technical Specifications

FORK	UPPER TUBE (mm)	WHEEL	TRAVEL (mm)	SPRING	BOTTOMLESS TOKENS		DAMPER	STEERER TUBE (in)	AXLE (mm)	OFFSET (mm)	AXLE TO CROWN (mm)	ROTOR DIAMETER MIN (mm)	ROTOR DIAMETER MAX (mm)	TIRE DIAMETER MAX (mm)	TIRE WIDTH MAX (mm)		
					INSTALLED	MAX											
ZEB Ultimate Flight Attendant FS-ZEB-UFA-A3 ZEB Ultimate FS-ZEB-ULT-A3 ZEB Select+ FS-ZEB-SELP-A3 ZEB Select FS-ZEB-SEL-A2 ZEB Base FS-ZEB-BSE-A2	38	27.5" B	150	DebonAir+ w/ ButterCups	2	5	Charger 3.1 Flight Attendant w/ ButterCups Charger 3.1 RC2 w/ ButterCups Charger 3.1 RC2	1.5 Tapered Alum 1.8 Tapered Alum†	15 x 110	38, 44	547	200	220	732 (F)	81		
			160		1						4					557	
			170			567											
			180			577											
			190			587											
		29" B	150	DebonAir+	2	5				Charger RC	566			44, 51		576	770 (F)
			160	DebonAir+	1					Charger R	586						
			170	0	4	596											
			180			606											
			190														

ZEB Select FS-ZEB-SEL-A2 ZEB Base FS-ZEB-BSE-A2	38	27.5" B	160	Dual Position Air	2	5	Charger RC	1.5 Tapered Alum 1.8 Tapered Alum†	15 x 110	38, 44	557	200	220	732 (F)	81	
			170		1	4					567					
			180		0						577					
		29" B	160		2	5	Charger R			576	44, 51			586		770 (F)
			170		1	4										
			180		0									596		

ASIAN HEADQUARTERS

SRAM Taiwan
No. 1598-8 Chung Shan Road
Shen Kang Hsiang, Taichung City
Taiwan

WORLD HEADQUARTERS

SRAM, LLC
1000 W. Fulton Market, 4th Floor
Chicago, Illinois 60607
U.S.A.

EUROPEAN HEADQUARTERS

SRAM Europe
Paasbosweg 14-16
3862ZS Nijkerk
The Netherlands