



- NOTES (UNLESS OTHERWISE SPECIFIED):
- SRAM RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE. USE LATEST REVISION.
  - REFERENCE DIMENSIONS NOTED WITH " ( ) " ARE FOR CUSTOMER DESIGN INFORMATION ONLY.
  - CROWN RACE  $\phi$ 'S MEASURED AS AVERAGE OF 3 DIAMETRIC POINTS MINIMUM.
  - HEADSET CUP ID MUST BE GREATER THAN STEER TUBE OD  $+0.3MM$  MIN
  - IMPORTANT: CUSTOMER IS RESPONSIBLE FOR ENSURING MINIMUM TIRE CLEARANCE. DO NOT EXCEED MAXIMUM TIRE ENVELOPE INDICATED ON THIS DRAWING.
  - POST TYPE BRAKE CALIPER MOUNT. DIRECT FOR 160MM ROTOR DIA. MAX ROTOR DIA. = 215MM.
  - ESTIMATED WORST CASE FRAME CLEARANCE
  - NOTE THAT POINT IS DEFINED IN 3 DIMENSIONS
  - WHEEL CENTER TOLERANCE: A-B <2MM  
DISHED WHEEL OR GAGE MUST BE CLAMPED IN DROPPOUTS  
9. 3D REPRESENTATION FILES (.IGS AND .STP) AVAILABLE UPON REQUEST.

DESIGNED BY: J. BALTES	FORMAT: A2	SCALE: 15	SHEET: 1 / 1
<p>LIFECYCLE STATUS</p> <p>CONFIDENTIAL - THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SRAM AND MAY BE REPRODUCED WITHOUT PERMISSION.</p> <p>RELEASED</p> <p>DRAWING NUMBER / DESCRIPTION</p> <p>USER SPECIFICATION, SID120, Q. 1 1/8</p>	<p>GEOMETRIC DIMENSIONING AND TOLERANCING PER ANSI Y14.5M-2018</p> <p>UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES</p> <p>THIS DRAWING IS THE PROPERTY OF SRAM AND SHALL BE RETURNED TO SRAM UPON REQUEST</p>	<p>98-4015-000-100</p> <p>98</p>	<p>A-3</p>

<p>ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED</p> <p>THIRD ANGLE PROJECTION</p> <p>THIS DRAWING IS THE PROPERTY OF SRAM AND SHALL BE RETURNED TO SRAM UPON REQUEST</p> <p>UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES</p>	<p>MATERIAL</p> <p>MA</p>	<p>98-4015-000-100</p>	<p>A-3</p>
--	---------------------------	------------------------	------------