



NOTES (UNLESS OTHERWISE SPECIFIED):

- SRAM RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE.
- REFERENCE DIMENSIONS NOTED WITH " () " ARE FOR CUSTOMER DESIGN INFORMATION ONLY.
- CROWN RACE \varnothing 'S MEASURED AS AVERAGE OF 3 DIAMETRIC POINTS MINIMUM.
- HEADSET CUP ID MUST BE GREATER THAN STEER TUBE OD +0.3MM.
- IMPORTANT: CUSTOMER IS RESPONSIBLE FOR ENSURING MINIMUM TIRE CLEARANCE. DO NOT EXCEED MAXIMUM TIRE ENVELOPE INDICATED ON THIS DRAWING.
- POST TYPE BRAKE CALIPER MOUNT, DIRECT FOR 160MM ROTOR DIA. MAX ROTOR DIA. = 215MM.
- FORK / FRAME CLEARANCE (WORST CASE)
- 3D REPRESENTATION FILES (.IGS AND .STP) AVAILABLE UPON REQUEST.

REV	REVISION RECORD
A	ECN 3004923 RELEASE

DESIGNED BY: J. BALTES	FORMAT: A2	SCALE: 1:10	SHEET: 1 / 1
SRAM LIFECYCLE STATUS: Released CONFIDENTIAL - THIS DRAWING CONTAINS INFORMATION THAT IS UNCLASSIFIED BY SRAM CORPORATION AND MAY BE REPRODUCED WITHOUT PERMISSION.			
ALL DIMENSIONS ARE mm UNLESS OTHERWISE NOTED TOLERANCES ARE PER ANSI Y14.5M 2018 DIMENSIONS IN PARENTHESES INDICATE THE DIMENSION IS FUNCTIONAL DIMENSIONS IN SQUARE BOXES INDICATE THE DIMENSION IS A TARGET DIMENSION DIMENSIONS IN CIRCLES INDICATE THE DIMENSION IS A POSITIONAL DIMENSION DIMENSIONS IN TRIANGLES INDICATE THE DIMENSION IS A PROFILE DIMENSION DIMENSIONS IN BRACKETS INDICATE THE DIMENSION IS A MAXIMUM DIMENSION		DRAWING NUMBER: US-4015-041-000 USER SPECIFICATION: SID TAPR MATERIAL: TITANIUM TYPING: A-2	